



Wright Technologies Inc.

Broadband Frequency Operation

TECHNICAL DATA SHEET

RoHS COMPLIANT

ASL18B-3015

0018

FEATURES

- * 1 GHz-18 GHz Frequency Operation
- * P-1dB: +15 dBm minimum
- * Small Signal Gain: 30-40 dB minimum
- * Gain Flatness: +/- 1.75 dB full band
- * High Output IP3: 25 dBm typ.
- * Noise Figure: 3.0 dB maximum
- * 50 Ohm Input and Output Matched
- * -20 to +55 °C Operating Temperature
- * Unconditionally Stable
- * Single DC Bias Supply
- * Built-in DC Voltage regulation
- * Small Size and Weight, Yet Robust

APPLICATIONS

Laboratory Applications
R&D Lab Use
Radar Systems
Electronic Warfare
Telecom Infrastructure

Test Instrumentation
Military and Space
Communications Systems
Satellite Communications
Wireless Communications

Microwave Radio Systems
Power Amplifier
General Purpose Amplifier
RF Front Ends
Fiber Optic Interface

Freq. In GHz	Gain dB	P-1 dBm	Input VSWR	Output VSWR	Noise dB
1.0	36.2	17.9	2.15	1.35	2.2
5.25	36.2	16.5	2.12	1.15	2.1
9.5	35.5	17.5	2.07	1.44	2.2
13.75	35.7	17.4	1.48	1.10	2.4
18.0	36.2	16.6	2.32	1.64	2.5
Min.	35.1	15.9	---	---	---
Max.	37.7	---	2.32	1.72	2.6
Spec.	30.0-40.0	15.0 Min	2.20 Typ	2.20 Max	3.0 Max

Bias @ +12.0 V, IT = $\frac{200}{225}$ mA
mA TYP

All Measurements Taken at 25°C Ambient Room

Wright Technologies Inc.
1352 Blue Oaks Blvd Suite 140
Roseville, CA 95678

Contact Us

Phone: (916) 773-4424
Fax: (916) 760-2770
E-mail: sales@wrighttec.com


DATA PLOTS

RoHS COMPLIANT


ASL18B-3015

0018

Gain



Power dBm




DATA PLOTS

RoHS COMPLIANT


ASL18B-3015

0018

Return Loss



Noise (1-2 GHz)





Wright Technologies Inc.

Broadband Frequency Operation

DATA PLOTS

RoHS COMPLIANT

ASL18B-3015

0018

Noise (2-18 GHz)

